TECHNICAL SPECIFICATION

Ventilation mode

IPPV, A/C, SIMV, SIGH, MANUAL

| Ventilator parameter range | | |
|---------------------------------------|---|--|
| Flowmeter | O ₂ (0.1~10 L/min) | |
| | N_2O (0.1 \sim 10 L/min) | |
| Rapid oxygen supply | 25 L/min~75 L/min | |
| Tidal volume (Vt) | 0, 20 mL~1500 mL | |
| Frequence | 1 /min~100 /min | |
| I:E | 2:1~1:6 | |
| PEEP | $0~\text{cmH}_2\text{O}\!\sim\!30~\text{cmH}_2\text{O}$ | |
| Pressure triggering sensitivity (Ptr) | $-20~cmH_2O\!\sim\!0~cmH_2O~(\text{Based on PEEP})$ | |
| Flow trigger sensitivity (Ftr) | 0.5 L/min~30 L/min | |
| | | |

0 (off) 1/100~5/100 OFF, 5s~60s

 $20~\text{cmH}_2\text{O}\!\sim\!100~\text{cmH}_2\text{O}$

| larm | and | protection |
|------|-----|------------|
|------|-----|------------|

| • | |
|---------------------------------------|---|
| The AC power failure alarm | Power failure or no connection |
| Low voltage alarm for back up battery | <11.3±0.3V |
| No tidal volume | ≤5mLwithin 6s |
| High oxygen concentration alarm | 19%~100% |
| Low oxygen concentration alarm | 18%~99% |
| High airway pressure alarm | $20~\text{cmH}_2\text{O}\!\sim\!100~\text{cmH}_2\text{O}$ |
| Low airway pressure alarm | $0~\text{cmH}_2\text{O}\!\sim\!20~\text{cmH}_2\text{O}$ |
| High minute volume alarm | Adult (5 L/min~20 L/min) |
| | Paed (1 L/min ~ 15 L/min) |
| Low minute volume alarm | 0~10 L/min |
| Continuous pressure alarm | (PEEP+1.5 kPa) over 16s |
| Suffocation warning | 5s~60s no spontaneous ventilation |
| The maximum limited pressure | <12.5 kPa |
| Fan error | Show on screen |
| Oxvaen deficit | Show on screen |

Monitoring parameter

| Frequence | 0 /min~100 /min |
|----------------------|-------------------|
| Tidal volume (Vt) | 0 mL~2000 mL |
| MV | 0 L/min~100 L/min |
| Oxygen concentration | 15 %~100 % |

| Working condition |
|-------------------|
|-------------------|

| Gas source | O ₂ , N ₂ O |
|-----------------|-----------------------------------|
| Pressure | 280 kPa∼600 kPa |
| Voltage | 100~240V |
| Power frequency | 50/60 Hz |

Packing size

SIGH

Apnea ventilation

Pressure limit

| Wooden case packing size | L 740* W 800* H 1460mm |
|--------------------------|------------------------|
| G.W. | 98KG |
| NW | 66KG |

Other models for your reference:

Oscillogram

P-T (pressure – time)
F-T (flow – time)











The picture is for reference only. For more information, please contact Superstar Medical sales representatives.





1 set vaporizer in standard, max 2 sets.

Application

The Anesthesia machine makes a good performance in Intensive Care Units (ICU), Operation room, Anesthesiology Department and other departments. HG6100D is designed for ease of use, incorporating basic function and the maximum patient safety in daily anesthesia practice. Professional design for adult, child and infant inhalation anesthesia and respiratory management, with advanced ventilation mode. Combine proven ventilation technology with the latest refinements in ergonomics and systems integration with an advanced, easy to use anesthesia table designed together with experienced experts to streamline your anesthesia workflow.



7" TFT screen



APL valve



Pressure gauge



Breathing circuit



S6100D with gray color

Trust point

- Providing customers with high quality and cost-effective anesthesia machine.
- The Superstar Medical team is a group of experienced and dedicated professionals with a passion for
- We listen to our customers and integrate their insights in our machine development. Flexible configurations to suit customers' needs.
- Countless feedback from customers give good reviews.
- Real time pressure-time, flow-time loop Oscillogram and high precision O₂ concentration detection function included.

Feature

- 7" TFT LCD screen displays the Ventilation parameters, Alarm information and Oscillogram.
- High precision flowmeter, instantly know the fresh gas flow to your patient.
- Integrated breathing circuit design, ensure easy operating and keep tidy.
- Multiple working modes such as volume control and pressure limit, adapt to wide range patient.
- Vaporizer with temperature, pressure, flow compensation and self-lock function, keep safety anytime.
- Multiple parameters monitoring interface, make every parameter clear, let users know the patient conditions in all aspects.
- Pressure-time, flow-time oscillogram show in real time.
- Vital sign monitor and Anesthetic gas monitor are optional.
- ACGO and fast oxygen supply Emergency use and revival after opertation.

Safety

- Three level alarm system, visual and sound alarm information.
- With multiple type of alarm, reminder and protection functions.
- Advanced power management control technology.
- Low O₂ pressure alarm and N₂O cut-off protection.