

HG-VHD202U 20x zoom HD COLOR PTZ Video Camera with USB video output



Product overview :

- 20x optical zoom
- Sleek and intelligent design
- Plug & Play USB2.0 Connectivity
- Crystal clear HD1080P image quality
- Preset: 9 via IR remote setting (256 via RS232)
- Wide field of view with no video distortion
- 1/3 inch high quality, 2.1MP (16:9) CMOS sensor
- Superior quality with Full Glass Lens Material
- Support ceiling mount, wall mount and tripod mount (Reverse mountable)
- 2D and 3D NR for best video quality in different lighting conditions
- Support Visca, Pelco-P, and Pelco-D protocol, RS232/RS485 Camera Control
- Compatible with most leading video conferencing software and platform
- Utilizing belt drive technology the PTZ is ultra-quiet and fast, while being very smooth

Product parameters:

Product No.	HG-VHD202U
Image Sensor	1/3 inch Exmor CMOS
Effective pixel	2.1 mega pixel (16:9)
Horizontal Resolution	1080p30/25, 720p30/25
Signal standard	NTSC/PAL
Zoom	20x optical zoom
Focal length	F=4.7mm(wide)-94.0(tele)
Horizontal Angle	Near-end 55.5° ~ Far-end 3.0°
Gain control	Auto/manual

Focus	Auto/manual
SNR ratio	≥50dB
Wide dynamic	D-WDR
Shutter speed	8to1/ 10000s(auto)
Preset position	IR remote control supports 9 presets PELCO Protocol supports 256 presets
Pan/Tilt movement range	Pan: 340°(max speed 80°/S), Tilt: 120°(max speed 60°/S)
Control terminal	RS-232, RS485
Control Protocol	VISCA, PELCO-D, PELCO-P (RS-232, RS485)
Video output	USB
Noise Reduction	2D/3D
Work temperature	-10°C~50°C
Storage temperature	-20°C~60°C
Baud rate	2400/4800/9600/19200bps
Decoder	Built-in
Address set	1~256
Installation	Support desktop, Tripod, Wall mount and Ceiling mount
Power supply	DC12 V/ 2A
Power consumption	12 W
Net weight/Gross weight	1.7kg/3.5kg
Dimension(LXWXH)	260*175*180 mm /296*255*218mm (before / after packing)
Accessories	DC 12V Power adaptor, IR remote control, Manual, RS232 cable, USB 2.0 cable, Ceiling brackets & screws.